

BKPoS

Stylish, Economic, Power Packed All in One PoS System

- ❖ Single / Dual Tone Housing
- ❖ 15inch LED Back-lit Display
- ❖ Variety of configurations: Celeron 1037, J1900, I3-3217U, I5-3317U & Android A9 & A17 CPU support
 - ❖ Frame or True-Flat Front Bezel
- ❖ Resistive or Projected Capacitive Touchscreen
 - ❖ LCD / VFD customer display
 - ❖ 9.7 / 12.1inch Second Display
- ❖ Integrated High Speed Printer , 200mm/sec
- ❖ Integrated Power Adapter for Cable management



Options:



LCD or VFD Customer Display
2 lines * 20 Characters



Magnetic Card Reader,
3 Tracks



High Speed Thermal Printer,
80/58mm, 200mm/sec



Frame Front Bezel
Resistive Touchscreen




9.7/12.1inch
Dual Display



12inch / 15.1inch
Operator Display

Specifications:

Display	15.1" LED Back lit, 4:3 Ratio			
Touch Panel	4 Wire Resistive Touch	4 Wire / 5 Wire Resistive Touch or Projected Capacitive Touch	4 Wire / 5 Wire Resistive Touch or Projected Capacitive Touch	Projected Capacitive Multi-Touch Touchscreen
Chipset	Intel NM70 Chipset	Intel Celeron Chipset	Intel NM70 Chipset	Android Chipset
Frame	Frame	Frame / True-flat	Frame / True-flat	True-flat
Master board	Fan-less J1800	Fan-less J1900	I3-3217U with Fan	Fan-less ARM Cortex A9
CPU	Integrated Intel® J1800/2.41GHz Dual core	Intel® Celeron® Processor J1900 (2M Cache,2 GHz)	Intel I3-3217 Dual core 1.8Ghz	Rock chip RK3188 ARM Cortex A9 Quad-Core
RAM	Standard 2GB DDR3 1333, 1* SO-DIMM DDRIII 800/1066MHZ, ((Max. Up to 4GB – 8GB(J1900N)			DDRIII 1GB (RK3188), 2GB(RK3288)
Storage	32G/64G SSD or 320/500Gb , 2.5"HDD	32G/64G SSD or 320/500Gb , 2.5"HDD	32G/64G SSD or 320/500Gb , 2.5"HDD	8G / 16G (RK3288) Upgradeable up to 32Gb
Video card	Intel HD Graphics 2500	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics
Network card	RTL8111F	RTL8111E	RTL8111E	10/100 Base T
Sound card	Realtek HD ALC662	Realtek ALC662	Realtek HD ALC662	MIC+Speaker+2x6W AMP
OS	Win 7,8,8.1, 10	Win 7,8,8.1, 10	Win 7,8,8.1, 10	Android 4.2.2 / Android 4.4.4
I/O Panel				
RS232 Ports	2	4	4	2
RS485	Optional	Optional	Optional	-
HDMI	1	Optional	1	1
USB	6	6	4	4
PS2 Mouse	1	-	1	-
PS2 Keyboard	1	-	1	-
LPT / Parallel	1	1	Optional	-
LAN	1	1	1	1
VGA	1	1	1	-
Wi-Fi & Bluetooth	NA	NA	NA	Built-in
TF Card Slot	NA	NA	NA	1
Environmental conditions				
Operating Temp	-10°C - +60°C	-10°C - +60°C	-10°C - +60°C	-10°C - +60°C
Operating Humidity	0% RH - 90%	0% RH - 95%	0% RH - 95%	0% RH - 95%
Storage Temp	-20°C - +70°C	-20°C - +70°C	-20°C - +70°C	-20°C - +70°C
Storage Humidity	10% RH - 90% RH	10% RH - 90% RH	10% RH - 90% RH	10% RH - 90% RH
Optional Features :				
POS Printer	Print Speed : 200mm/sec, Paper Size : 80 /58mm, Interface : USB+RS232 OPOS Compliant, ESC/POS Compliant, Support 256K NV Logo download and print			
MSR	3 Track, USB Interface			
Second Display	9.7 / 12.1inch Display (1024 x 768 Resolution)			
Customer Display	LCD (2*20) / VFD (2*20), RS232 Interface			
Speakers	2* 6 Amp			
Certification	FCC, CE, ROHS			
Dimensions	40 x 22 x 22cm			
Packing weight	44.5 x 33.5 x 48.5cm, 8kgs (w/o Printer)			

© 2012 PoS Tektronics Limited. The information contained herein is subject to change without notice. PoS Tektronics Limited shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Intel, Core, is trademarks or registered trademarks of Intel Corporation or its subsidiaries in the U.S. and other countries. Please visit relevant websites for more information



PoS Tektronics Limited

Rooms 1318-19, 13 / F, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong

Email: pcpes@yahoo.com