

POS1AP

True Flat POS Workstation

- ❖ 15inch LED Back-lit Display
- ❖ Variety of configurations: Celeron 1037, J1800, J1900, I3-3217U, I5-3317U & Android A9 & A17 CPU support
- ❖ Frame or True-Flat Front Bezel
- ❖ Resistive or Projected Capacitive Touchscreen
- ❖ LCD / VFD customer display
- ❖ Integrated Power Adapter for Cable management



Options:



LCD or VFD Customer Display
2 lines * 20 Characters



Magnetic Card Reader,
3 Tracks



Frame Front Bezel
Resistive Touchscreen



Integrated Power Adapter

Specifications:

Display	15.1" LED Back lit, 4:3 Ratio			
Touch Panel	4 Wire Resistive Touch	4 Wire / 5 Wire Resistive Touch or Projected Capacitive Touch	4 Wire / 5 Wire Resistive Touch or Projected Capacitive Touch	4 Wire / 5 Wire Resistive Touch or Projected Capacitive Touch
Chipset	Intel NM70 Chipset	Intel Celeron Chipset	Intel NM10 Chipset	Intel NM70 Chipset
Frame	Frame / True Flat	Frame / True Flat	Frame / True Flat	Frame / True Flat
Master board	Fan-less J1800	Fan-less J1900	Fan-less N2800	I3-3217U with Fan
CPU	Integrated Intel@J1800/2.41GHz Dual core	Intel@ Celeron@ Processor J1900 (2M Cache,2 GHz)	Intel@ Atom dual core N2800 (1.86GHz)	Intel I3-3217 Dual core 1.8Ghz
RAM	Standard 2G DDR3 1333, 1* SO-DIMM DDRIII 800/1066MHz, Max. Up to 4GB – 8GB(J1900N)			
Storage	32G/64G SSD or 320/500Gb , 2.5"HDD	32G/64G SSD or 320/500Gb , 2.5"HDD	32G/64G SSD or 320/500Gb , 2.5"HDD	32G/64G SSD or 320/500Gb , 2.5"HDD
Video card	Intel HD Graphics 2500	Intel HD Graphics	Intel@ GMA3600	Intel HD Graphics
Network card	RTL8111F	RTL8111E	RTL8111E	RTL8111E
Watch Dog Timer	NA	NA	Support hardware reset function (L256, 0~255 seconds)	NA
Sound card	Realtek HD ALC662	Realtek ALC662	Realtek HD ALC662	Realtek HD ALC662
I/O Panel				
RS232 COM ports	2	4	4	4
RS485	Optional	Optional	Optional	Optional
HDMI	1	Optional	Optional	1
USB	4	6	4	4
PS2 Mouse	1	-	1	1
PS2 Keyboard	1	-	1	1
LPT / Parallel	1	1	1	Optional
LAN	1	1	1	1
VGA	1	1	1	1
Environmental conditions				
Operating Temp	-10°C - +60°C	-10°C - +60°C	-10°C - +60°C	-10°C - +60°C
Operating Humidity	0% RH - 90%	0% RH - 95%	0% RH - 95%	0% RH - 95%
Storage Temp	-20°C - +70°C	-20°C - +70°C	-20°C - +70°C	-20°C - +70°C
Storage Humidity	10% RH - 90% RH	10% RH - 90% RH	10% RH - 90% RH	10% RH - 90% RH
Packaging Dimensions				
G.W	9kg			
Packing size	42*41*26cm			

© 2012 PoS Tektronics Limited. The information contained herein is subject to change without notice.

PoS Tektronics Limited shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Intel, Core, is trademarks or registered trademarks of Intel Corporation or its subsidiaries in the U.S. and other countries. Please visit relevant websites for more information



PoS Tektronics Limited

Rooms 1318-19, 13 / F, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong

Email: pcpes@yahoo.com