

Parallel Flex L/L+

Edge light



L6/L6+

MEASURES	404 x 24 x 14 mm (15.91 x 0.94 x 0.55 in)	
VOLTAGE	24 V	
POWER CONS.	L6 15.8 W	L6+ 21 W
LED COLOR	6,500K	
LUMEN	L6 ≈ 1,890 lm	L6+ ≈ 2,356 lm
LIGHT EFFIC.	L6 ≈ 120 lm/W	L6+ ≈ 112 lm/W
LIGHT BEAM	10° and 42°	
CRI	> 80%	

L3/L3+

MEASURES	194 x 24 x 14 mm (7.64 x 0.94 x 0.55 in)	
VOLTAGE	24 V	
POWER CONS.	L3 8 W	L3+ 10.8 W
LED COLOR	6,500K	
LUMEN	L3 ≈ 967 lm	L3+ ≈ 1,205 lm
LIGHT EFFIC.	L3 ≈ 121 lm/W	L3+ ≈ 112 lm/W
LIGHT BEAM	10° and 42°	
CRI	> 80%	

L2/L2+

MEASURES	124 x 24 x 14 mm (4.88 x 0.94 x 0.55 in)	
VOLTAGE	24 V	
POWER CONS.	L2 5.8 W	L2+ 7.8 W
LED COLOR	6,500K	
LUMEN	L2 ≈ 635 lm	L2+ ≈ 756 lm
LIGHT EFFIC.	L2 ≈ 110 lm/W	L2+ ≈ 97 lm/W
LIGHT BEAM	10° and 42°	
CRI	> 80%	

OTHER INFO:

LIFE SPAN	> 54,000 Hours
T_p MAX.	85°C
% FAILURES	Category F10
LUMINOUS FLUX	Category A L90
CHROM. COORD.	4-step MacAdam Ellipse



All rights reserved. The information in this document is subject to change without notice.
Manufactured in our installations in Barcelona, Spain.
C/ Josefina Vidal Folch 1-3, 08930 Barcelona (+34) 935 334 600 - www.actilum.com

Actilum Lux