

# Compuprint 6010

With Compuprint 6010 on hand, label printing becomes so simple between your fingertips.

Compuprint 6010 is powered by high capacity lithium-ion battery, armored with water/dust/ shock resistant feature, supported with drop-and-fit design; it is your ultimate weapon to take on the challenges from mobile applications in retail / warehouse & storage / parking receipt industry and many more.



- Ultra light, compact and portable
- Rugged design passed 1.5m drop test
- Bluetooth 4.0/BLE Dual Mode
- USB charging at your convenience
- Long-lasting battery life (5 days stand-by)
- Support various of 1D & 2D barcode printing
- Multiple wireless interfaces: support Android, WinCE, iOS
- OLED display
- Built-in Magnetic Card Reader as specific model



Rugged Design



Easy Wireless Connection



OLED Screen





**COMPUPRINT WE PRINT YOUR IDEAS**

Specification

Item	Parameter	
Printing	Printing Method	Direct Thermal Line Printing
	Resolution	203dpi (8dots/mm)
	Printing Speed	Max.110mm/s
	Printing Width	48mm
	Interface	USB, Bluetooth 4.0
Power Saving	Sleep Mode	YES
Memory	RAM	32Mb
	Flash	64Mb
Resident Fonts	Font	FONT A 12X24;FONTB 8X16; CHN 24X24;16X16;
	Alphanumeric	95
	Codepage	48
Barcode	1D	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Graphics	Support bitmap printing with different density and user defined bitmap printing	
Detection	Sensors	Paper out/Black mark/Gap label sensor, Cover open switch
LED indicator	Power Indicator	Green
	Error Indicator	Red

Power	Input	AC 100 -240V
	Output	DC 5V/1A
	Battery	1300mAh/7.4V rechargeable Li-ion battery
Paper	Paper Type	Continuous paper, black mark paper, linerless label, gap label
	Paper Width	58mm
	Paper Thickness	0.053~0.1mm
	Paper Roller Diameter	≤40mm
	Paper Loading	Easy paper loading
Environment	Operation	-5°C~50°C , 25%~85%RH
	Storage	-20°C~70°C, 5%~95%RH
Physical Characteristics	Dimension	126.9(L)*84.4(W)*50.6(H)mm
	Weight	234 g. (Without paper roll)
Options & Accessories	USB Cable, Belt Clip, Charger ,Paper Roll, Quick Start Guide, CD	
Software	Emulation	ESC/POS
	Driver	Windows XP/Vista/7/8/10/Linux/OPOS
	SDK	WinCE, Win Mobile, Android, iOS



**Compuprint S.r.l.**

Via Cottolengo 75-77-79  
10072 Caselle T.se (TO)

Sales Contact

Tel. +39 011 9892 141 - Fax +39 011 9974432

sales@compuprint.com

[www.compuprint.com](http://www.compuprint.com)